

## BONANZA

<b>Manufacturing process</b>	Tufted		ISO 2424
<b>Gauge</b>	5/32" Loop		
<b>Pilecomposition</b>	100% PP		ISO 2424
<b>Primary backing</b>	Woven PP		ISO 2424
<b>Secondary backing</b>	AB + Felt		ISO 2424
<b>Width</b>	400 cm, 500 cm	± 1%	EN 986
<b>Pile weight</b>	approx. 360 gr/m <sup>2</sup>		ISO 8543
<b>Total weight</b>	AB : approx. 1496 gr/m <sup>2</sup> Felt : approx. 1498 gr/m <sup>2</sup>	± 15%	ISO 8543
<b>Pile height</b>	approx. 3,5 mm		ISO 1765
<b>Total height</b>	AB : approx. 5,3 mm Felt : approx. 6,0 mm	+ 15% / -10%	ISO 1765
<b>Number of knots</b>	approx. 106.155 /m <sup>2</sup>	+ 10% / -7,5%	ISO 1763
<b>Fire classification</b>	AB : Efl Felt : Efl		EN 13501-1
<b>Light fastness</b>	≥ 5		105-B02
<b>Wearability</b>	≥ 4		105-X12
<b>Water fastness</b>	≥ 4		105-E01
<b>Thermal resistance</b>	0,120 m <sup>2</sup> K/W		ISO 8302
<b>Sound insulation</b>	0,10 dB		ISO 10140
<b>GUT Nr.</b>	Felt : 95BAF8E6		

## Floorsymbols Felt



## Certificates

